

HOW TO ORDER

STEP 1 » Choose Recessed Poke-Through (MOI4-REC)



STEP 2 » Choose Configuration *

**Configuration does not include communication components*

	COMM10 » Ten communication openings		PWR2-COMM5 » (2) single receptacle & (5) communication openings
	DP1 » Decora receptacle		PWR2-COMM6 » (2) single receptacle & (6) communication openings
	DP1-COMM4 » Decora receptacle & (4) communication openings		PWR4 » (4) single receptacle
	PASS-THROUGH » 2.5" trade size circular opening		PWR4-COMM4 » (4) single receptacle & (4) communication openings
	PWR2-COMM4 » (2) single receptacle & (4) communication openings		SYS-COMM » Systems furniture communication-power & comm cabling
	PWR2-COMM4-DB15 » (2) single receptacle & (4) communication openings & (1) DB-15 opening		AV-COMM4 » (1) Decora opening for CI-5BWPA (4) communication openings

EXAMPLE:

MOI4-REC-DP1

STEP 3 » Choose Cover Finish (AHC-CED Cover only for MOI4-REC)

Stainless Steel
Add: **-SS**

Brass
Add: **-BR**

Black
Add: **-BK**

STEP 4 » Specify Slab Thickness

» Must specify when ordering to achieve proper collar size of threaded pipe

** Minimum slab thickness for Recessed Poke-Through MOI4-REC is 6 inches

EXAMPLE

